

HCT-680

六轴数控高速卷簧机


6 Axis CNC High-speed Spring Coiling Machine







External/Internal spring length gauge 外置/内置检长系统





▼ 产品介绍 Description

HCT-680六轴数控高速卷簧机由6个日本伺服马达和益图电脑控制系统组成,各轴可独立和同步运作。公司设计团队在创新和改 进方面做了重大改革,真正实现了人机对话,具备一分钟弹簧成型,速度高,精度准,噪音低,节省了调试时间及线材成本等特 点,有直切,对切,摆切,高清摄影检长功能。

HCT-680 6-axis High speed Spring Coiling Machine is composed by 6 Japan motor and TaiWan control system, each axis can work independently and synchronously. Our design team made a lot of improvement and innovation with more function and higher automation degree. This updated machine can form the spring within one minute, which owns the features of easy to operate, high precision and low noise. It can save much testing spring time and the cost of the raw material. This machine also has the function of straight cutting, subtend cutting and Rotary cutting.



技术参数 Specification

| Model | HCT-680 |
|-----------------------------|-------------------|
| 轴数 Number of Axis | 6 轴 (axis) |
| 加工线径 Wire Size Range | Ф3.0-8.0 mm |
| 最大弹簧外径 Max Outside Diameter | Ф 120 mm |
| 最大弹簧螺距 Max Pitch of Spring | 100 mm |
| 最大送线速度 Max Feeding Speed | 60 m/min |
| 卷绕比 Spring Index | 4 |
| 送线轮组数 Feeding Roller Pairs | 4组(Pairs) |
| 送线伺服电机 Feeding Motor | 30.0 kw |
| 上切刀伺服电机 Upper Cutter Motor | 7.5 kw |
| 下切刀伺服电机 Under Cutter Motor | 7.5 kw |
| 凸轮伺服电机 Cam Motor | 2.7 kw*2 |
| 螺距伺服电机 Pitch Motor | 2.7kw |
| 电源 Power | 3P 380V 50HZ |
| 机器尺寸 Dimension (LxWxH) | 2000x2100x2200 mm |
| 机器重量 Weight | 6000 kg |

以上参数如有变更, 恕不另行通知

Notice shall not be given in case alteration of parameters, please excuse.